



## SAE 10W-30 Motor Oil

**Description** Pride Plus Advantage Premium 10W-30 Motor Oil is premium engine oil that is formulated for turbo-charged and naturally aspirated gasoline, propane, natural gas engines in passenger car and light duty truck service. The SAE 10W-30 meets or exceeds the API SM classification and also meets the requirements of ILSAC Starburst GF-4. This oil is designed for use in U.S., European, and Japanese passenger cars, vans, sport utility vehicles and light duty trucks.

- Features**
- Meets or exceeds API Service SM.
  - Meets or exceeds ILSAC Starburst GF-1, GF-2, GF-3 AND GF-4 requirements.
  - Meets passenger car and light truck manufacturers warranty requirements.
  - Lubricates, cools, and protects turbo-charged high-revving engines that operate at high temperatures.
  - Protects the engine in controlling varnish, deposits, rust, corrosion, wear, and cleanliness.
  - Designed to flow at low temperatures to get to vital engine parts quickly.

- Applications**
- Passenger car and truck gasoline, propane, and natural gas engines specifying API service SF, SG, SH, SJ, SL, and SM engine oils.
  - Maintains the warranty requirements for today's passenger car and light duty trucks specifying ILSAC Starburst GF-4 engine oils.
  - Reduces high temperature oxidation.
  - Energy-Conserving for improved fuel economy.
  - API Certification License #2325.

|                           |                                    |       |
|---------------------------|------------------------------------|-------|
| <b>Typical Properties</b> | cSt @ 40° C (D445)                 | 69.43 |
|                           | cSt @ 100° C (D445)                | 10.52 |
|                           | Viscosity Index (D2270)            | 139   |
|                           | CCS Viscosity (D2602), cP @ -25° C | 5900  |
|                           | Flash Point (D92), ° C             | 202   |
|                           | Pour Point, (D97), ° C             | -36   |
|                           | Noack Volatility                   | 14.0  |
|                           | Color (ASTM D1500)                 | 3     |
|                           | Zinc (ASTM D5185)                  | 890   |
|                           | Phosphorus (ASTM D5185) ppm        | 750   |
|                           | TBN                                | 7.6   |