



## Tractor Hydraulic Fluid

**Description** Pride Plus Advantage Tractor Hydraulic Fluid is formulated as a multi-purpose high quality fluid for use in hydraulic, final drive, wet brake, transmission differential, and power steering systems commonly used in farm tractors and other off road equipment.

It meets the performance requirements of all major brands of tractors and farm equipment, providing excellent wear protection, seal compatibility, corrosion protection, gear pitting protection and proper operation of wet brakes and clutches.

### Applications

| <u>Manufacturer</u>     | <u>Specification</u>  |
|-------------------------|---|
| Allis Chalmers          | S25743, PF 821  |
| Allison (DDC)           | C3, C4  |
| Caterpillar             | Power Shift transmission specifying Cat TO2   |
| John Deere              | J20C, J20B, HyGard J14B/C, type 303, Quatrol  |
| Deutz Allis             | HTF(PF821), 821XL   |
| Ford New Holland        | M2C134-A/B/C/D, M2C86-B/C, M2C53-A, M2C41-B   |
| International Harvester | B-6 (HY-TRAN)   |
| J.I. Case               | MS-1209 (HY-TRAN ULTRA), MS-1210 (HY-TRAN PLUS)<br>MS-1204, MS-1205, MS-1206, MS-1210 (TCH), AND B-6, TFD |
| KUBOTA                  | Universal Transhydraulic Fluid (UTD)  |
| Massey-Ferguson         | M1110, M1127 A/B, M1135, M1141 (Permatran III)  |
| Oliver                  | Type 55   |
| White Farm Equipment    | Q1766B, Q1826, Q1802, Q1705, Q1722  |

### Typical Properties

|                     |         |
|---------------------|---------|
| Viscosity @100C cSt | 9.3     |
| Viscosity @ 40C cSt | 58.5    |
| Viscosity Index     | 140     |
| Pour Point, C       | -36     |
| Flash Point, C/F    | 215/430 |
| Color (ASTM)        | 1.5     |

**NOTE:** The values are representative of current production and may vary within modest ranges.

[www.hutchenspetro.com](http://www.hutchenspetro.com)

P.O. Box 272 • 22 Performance Drive • Stuart, VA 24171  
(276) 694-7000 • 1-800-537-7433 • Fax (276) 694-3382